


PRO SERIES

REPLACEMENT WINDOWS



960 SLIDING PATIO DOOR



NEW!
**DUAL WALL
FLUSH FIN**

BUILT TO LAST. MADE TO IMPRESS.

You have a vision for how you want your replacement doors to look. Ply Gem Windows Pro Series can help you realize that vision. Every window and door is designed to fit your needs. You'll find the right sizes, the right designs and the right solutions to help make your window and door replacement project a success.

* This product can be configured to meet or exceed Federal Energy Tax Credit requirements.



960 SLIDING PATIO DOOR



PLY GEM PRO SERIES 960 SLIDING PATIO DOORS HAVE BEEN GREEN APPROVED BY THE NAHB RESEARCH CENTER.

This means you can be assured that Ply Gem Pro Series 960 sliding patio doors comply with specific green practice criteria in the National Green Building Standard. Visit www.GreenApprovedProducts.com for more details.

THERMAL PERFORMANCE

	R Value	NFRC CERTIFIED		
		U Value	SHGC	VT
WITH WARM EDGE				
3/4" Clear	2.13	0.47	0.61	0.64
3/4" HP	3.33	0.30	0.28	0.54
3/4" HP ^{SC}	3.33	0.30	0.22	0.42
WITH WARM EDGE+				
3/4" HP	3.45	0.29	0.28	0.54
3/4" HP ^{SC}	3.45	0.29	0.22	0.42

All units tested in accordance with ASTM standards; rated in accordance with International Residential Code; and witnessed by an independent NAMI accredited lab. Performance values reflect the performance of units tested with the following configuration: 3/4" IGU, 3mm glass and no grilles.



R VALUE: Restrictive ambient air flow; U VALUE: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

STANDARD FEATURES

- Dual wall flush fin for enhanced strength and enduring beauty
- Maintenance-free multi-chamber New Generation PVC vinyl construction with fusion welded corners for durability, weather-tight performance and beauty
- Smooth gliding stainless steel rollers provide long lasting durability
- Two-point lock with adjustable strikes is standard on 2-panel and 3-panel doors and four-point lock is standard on 4-panel doors
- Energy-efficient warm edge insulating tempered glass for enhanced energy performance
- Shoot-bolt in 4-panel doors for added security
- 4 3/8" frame depth with heavy vinyl walls for strength and stability
- Anodized aluminum threshold cover



OPTIONS

GLASS OPTIONS:

HP glass, HP^{SC} glass, Warm Edge+, STC options, tints, obscure, laminated, wire, single glaze



GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in flat 5/8", sculptured 5/8" or 1" styles; simulated-divided-lite (SDL) in 1/8" or 1 1/4" styles; 2" accent bar



HARDWARE OPTIONS:

Exterior: white or beige; *Interior:* white, beige, polished brass, antique brass, satin nickel, oil rubbed bronze or polished chrome



FRAME OPTIONS:

Dual wall flush fin, no fin, 1 3/8" nail fin setback with stucco key or J-channel

COLOR OPTIONS:



NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

1. Most units are rated DP40 standard.
2. Low-E with argon.
3. Optional Solar Cooling optimized Low-E with argon.
4. Optional Sound Control.
5. Optional Warm Edge+ spacer upgrade for enhanced performance.

