ODORLESS MINERAL SPIRITS MATERIAL SAFETY DATA SHEET FOR USA AND CANADA



SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ODORLESS MINERAL SPIRITS

SYNONYMS: Not available.

PRODUCT CODE: 6643, 6657

PRODUCT USE: Parts cleaning and general use (such as paint thinner).

If this product is used in combination with other products, refer to the

Material Safety Data Sheets for those products.

This number is for emergency use only. If you desire non-emergency product information, please call a phone number listed below.

24-HOUR EMERGENCY PHONE NUMBER MEDICAL AND TRANSPORTATION (SPILL):

1-800-468-1760

SUPPLIER: Safety-Kleen Systems, Inc.

5400 Legacy Drive Cluster II, Building 3 Plano, Texas 75024

USA

1-800-669-5740

www.Safety-Kleen.com

TECHNICAL INFORMATION: 1-800-669-5740 Press 1 then 1, then Extension 7500

MSDS FORM NUMBER: 82739 ISSUE: August 3, 2007

ORIGINAL ISSUE: March 27, 1998 SUPERSEDES: December 13, 2005

PREPARED BY: Product MSDS Coordinator APPROVED BY: MSDS Task Force

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

APPEARANCE

Colorless to pale yellow liquid, faint hydrocarbon odor.

WARNING!

PHYSICAL HAZARDS

Combustible liquid and vapor.

HEALTH HAZARDS

May be harmful if swallowed.

May irritate the eyes and skin.

Contains material that may cause central nervous system effects.

ENVIRONMENTAL HAZARDS

Not expected to be harmful to the environment.

POTENTIAL HEALTH EFFECTS

INHALATION This product is not likely to present an inhalation hazard at normal (BREATHING): temperatures and pressures. However, when aerosolizing, high

concentrations of aerosol or vapor may irritate the respiratory tract (nose, throat, and lungs). High concentrations of vapor or mist may cause nausea, vomiting, headaches, dizziness, loss of coordination, numbness, and other central nervous system effects. Massive acute overexposure may cause rapid central nervous system depression, sudden collapse, coma, and/or death.

EYES: May cause irritation.

SKIN: May cause irritation. Not likely to be absorbed through the skin in harmful

amounts.

INGESTION (SWALLOWING):

May be harmful if swallowed. May cause throat irritation, nausea, vomiting, diarrhea and central nervous system effects as noted under **INHALATION** (**BREATHING**). Aspiration hazard: breathing product into the lungs during

ingestion or vomiting may cause lung injury and possible death.

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

MEDICAL CONDITIONS
AGGRAVATED BY

Individuals with pre-existing respiratory tract (nose, throat, and lungs), central nervous system, eye, and/or skin disorders may

EXPOSURE: have increased susceptibility to the effects of exposure.

CHRONIC: Prolonged or repeated inhalation may cause toxic effects as noted under

INHALATION (BREATHING). Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying,

cracking, redness, itching, and/or swelling (dermatitis).

CANCER No known carcinogenicity. For more information, see **SECTION 11**:

INFORMATION: CARCINOGENICITY.

Also see **SECTION 15: CALIFORNIA**.

POTENTIAL ENVIRONMENTAL EFFECTS

Not expected to be harmful to the environment. Also see **SECTION 12: ECOLOGICAL INFORMATION**.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	Component	Synonyms	Percent
64741-65-7	Naphtha (petroleum), heavy alkylate	N.Av.	100

SECTION 4: FIRST AID MEASURES

INHALATION (BREATHING):

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if

breathing difficulty persists.

EYES: If irritation or redness from exposure to vapor develops, move away from

exposure into fresh air. Upon contact, immediately flush eyes with plenty of lukewarm water, holding eyelids apart, for 15 minutes. Get medical

attention.

SKIN: Remove affected clothing and shoes. Wash skin thoroughly with soap and

water. Get medical attention if irritation or pain develops or persists.

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

INGESTION (SWALLOWING): Do NOT induce vomiting. Immediately get medical attention. Call 1-800-468-1760 for additional information. If spontaneous vomiting occurs, keep head below hips to avoid breathing the product into the lungs. Never give

anything by mouth to an unconscious person.

NOTE TO PHYSICIANS: Treat symptomatically and supportively. Administration of gastric lavage, if warranted, should be performed by qualified medical personnel. Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760 for additional information.

SECTION 5: FIRE FIGHTING MEASURES

HAZARDOUS COMBUSTION

PRODUCTS:

Decomposition and combustion materials may be toxic. Burning may produce carbon monoxide, and unidentified organic compounds.

CONDITIONS OF FLAMMABILITY:

Heat, sparks, or flame.

PROTECTIVE EQUIPMENT

FOR FIREFIGHTERS:

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for


fire emergencies.

EXTINGUISHING MEDIA:

Carbon dioxide, regular foam, dry chemical, water spray, or water fog. Water or foam may cause frothing.

NFPA 704 HAZARD IDENTIFICATION:

This information is intended solely for the use by individuals trained in this system.



FIRE FIGHTING INSTRUCTIONS: Keep storage containers cool with water spray.

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

FIRE AND EXPLOSION HAZARDS:

Vapor explosion hazard indoors, outdoors, or in sewers. Vapor may travel to ignition source and flashback. Vapors will spread along the ground and collect in low or confined areas. Run-off to sewer may create a fire or explosion hazard. Heated containers may rupture, explode, or be thrown into the air. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact. Product may be sensitive to static discharge, which could result in fire or explosion.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. A vapor suppressing foam may be used to reduce vapors. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean tool into a sealable container for disposal.

Additionally, for large spills: Water spray may reduce vapor, but may not prevent ignition in closed spaces. Dike far ahead of liquid spill for collection and later disposal.

SECTION 7: HANDLING AND STORAGE

HANDLING:

Keep away from heat, sparks, or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean, sparkproof tools and explosion-proof equipment. When transferring product, metal containers, including trucks and tank cars, should be grounded and bonded. Do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes. Do not smoke while using this product.

SHIPPING AND STORING:

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition; containers may explode and cause injury or death. Empty product containers may retain product residue and can be dangerous. See **SECTION 14: TRANSPORTATION INFORMATION** for Packing Group information.

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES:

Component Exposure Limits

Naphtha (petroleum), heavy alkylate (64741-65-7)

ACGIH: 100 ppm TWA (related to Stoddard solvent)

OSHA: 100 ppm TWA; 525 mg/m3 TWA (related to Stoddard solvent)

NIOSH: 350 mg/m3 TWA (related to Stoddard solvent)

1800 mg/m3 Ceiling (15 min) (related to Stoddard solvent)

ENGINEERING CONTROLS:

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits. Where explosive mixtures may be present, equipment safe for such

locations should be used.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION:

Use NIOSH-certified, full-face, air-purifying respirator with organic vapor cartridges respiratory protective equipment whenever concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.

EYE

Where eye contact is likely, wear chemical goggles; contact lens use is not

PROTECTION: recommended.

SKIN

Where skin contact is likely, use chemical resistant gloves; use of natural

PROTECTION: rubber or equivalent gloves is not recommended.

To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, coveralls, long

sleeve shirts, or other protective clothing.

PERSONAL HYGIENE:

Use good personal hygiene. Wash thoroughly with soap and water after handling product and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse. Discard affected clothing, shoes, and/or protective equipment if they cannot be thoroughly cleaned. Discard leather articles, such as shoes, saturated with this product.

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

OTHER Where spills and splashes are likely, facilities storing or using these products

PROTECTIVE should be equipped with an emergency eyewash and shower, both

EQUIPMENT: equipped with clean water, in the immediate work area.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE, Colorless to pale yellow liquid, faint hydrocarbon odor.

APPEARANCE, AND ODOR:

ODOR THRESHOLD: Not available

MOLECULAR WEIGHT: Not applicable

SPECIFIC GRAVITY: 0.76 (water = 1) (approximately)

DENSITY: 6.3 LB/US gal (760 g/l) (approximately)

VAPOR DENSITY: Not available

VAPOR PRESSURE: 1.9 mm Hg @ 100°F (38°C)

BOILING POINT: 340°F (171°C) (initial)

FREEZING/MELTING POINT: Not available

pH: Not applicable

EVAPORATION RATE: Less than 1 (butyl acetate = 1)

SOLUBILITY IN WATER: Insoluble.

FLASH POINT: 109°F (43°C) (minimum) Closed Cup

FLAMMABLE LIMITS IN AIR: LOWER: 0.7 VOL% UPPER: 7 VOL%

AUTOIGNITION TEMPERATURE: Not available.

% VOLATILE: Negligible

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal temperatures and pressures.

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

CONDITIONS TO

AVOID:

Spark, flame and incompatible materials.

INCOMPATIBILITY: Avoid acids and oxidizing agents.

REACTIVITY: Polymerization is not known to occur under normal temperature and

pressures. Not reactive with water.

HAZARDOUS DECOMPOSITION None under normal temperatures and pressures. See also **SECTION 5**: **HAZARDOUS COMBUSTION PRODUCTS**.

PRODUCTS:

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICITY DATA:

Component Analysis - LD50/LC50 Naphtha (petroleum), heavy alkylate (64741-65-7)

Inhalation LC50 Rat: >5.04 mg/L/4H

Oral LD50 Rat: >7000 mg/kg Dermal LD50 Rat: >3000 mg/kg Dermal LD50 Rabbit: >2000 mg/kg

ACUTE EFFECTS: May be irritation to skin, eyes and respiratory tract. High

concentrations of vapor or mist may cause nausea, vomiting, headaches, dizziness, loss of coordination, numbness, and other central nervous system effects. May be harmful if swallowed. May cause throat irritation, nausea, vomiting, diarrhea and central nervous system effects. Aspiration hazard: breathing product into the lungs during ingestion or

vomiting may cause lung injury and possible death.

REPEATED DOSE EFFECTS: Based on best current information, there is no known

reproductive toxicity associated with this product.

Based on best current information, there is no known

teratogenicity associated with this product.

Based on best current information, there is no known human

sensitization associated with this product.

Based on best current information, there is no known

mutagenicity associated with this product.

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

CARCINOGENICITY: Based on best current information for the components in

Section 2, there is no known carcinogenicity as categorized by ACGIH A1 or A2 substances; as categorized by IARC Group 1, Group 2A, or Group 2B agents; or as listed by NTP as either known carcinogens or substances for which there is limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals.

Also see **SECTION 15: CALIFORNIA**.

TARGET ORGAN EFFECTS: Prolonged or repeated eye contact may cause inflammation

of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling

(dermatitis).

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY: Not available.

Component Analysis - Ecotoxicity - Aquatic Toxicity

Naphtha (petroleum), heavy alkylate (64741-65-7)

Test & Species Conditions

72 Hr EC50 Selenastrum capricornutum 30000 mg/L

PERSISTENCE/DEGRADABILITY: Not expected to persist.

BIOACCUMULATION/ACCUMULATION: Not expected to bioaccumulate.

MOBILITY IN ENVIRONMENTAL Not known.

MEDIA:

OTHER ADVERSE EFFECTS: Not available. Also see SECTION 12: ECOLOGICAL

INFORMATION.

OCTANOL/WATER

PARTITION COEFFICIENT: Not available.

VOLATILE ORGANIC COMPOUNDS: 100 WT%; 6.3 LB/US gal; 760 g/l (approximately)

As per 40 CFR Part 51.100(s).

SECTION 13: DISPOSAL CONSIDERATIONS

DISPOSAL: Dispose in accordance with federal, state, provincial, and local regulations.

Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-

Kleen regarding proper recycling or disposal.

CODE(S):

USEPA WASTE If discarded, this product is considered a RCRA ignitable waste, D001.

Based on available data, this information applies to the product as supplied to the user. Processing, use, or contamination by the user may change the

waste code applicable to the disposal of this product.

SECTION 14: TRANSPORT INFORMATION

Shipping Name: Combustible Liquid, n.o.s. (Naptha petroleum, heavy alkylate) DOT:

UN/NA #: NA1993 Hazard Class: Combustible Liquid Packing Group: III

Additional Info.: If transported by method other than highway or rail:

Petroleum Product, n.o.s. (Naptha petroleum, heavy alkylate), 3, UN1268, PG III

Shipping Name: Petroleum Product, n.o.s.(Naptha petroleum, heavy alkylate) TDG:

UN/NA #: UN1268 Hazard Class: 3 Packing Group: III

Required Label(s): FLAMMABLE LIQUID

EMERGENCY RESPONSE

Reference North American Emergency Response Guidebook **GUIDE NUMBER:**

SECTION 15: REGULATORY INFORMATION

USA REGULATIONS

SARA SECTIONS 302 AND 304:

Based on the ingredients listed in **SECTION 2**, this product does not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

SARA SECTIONS 311 AND 312:

This product poses the following health hazards as defined in 40 CFR Part 370 and is subject to the requirements of sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA):

Immediate (Acute) Health Hazard Delayed (Chronic) Health Hazard

Fire Hazard

Revision 08/07; MSDS Form No. 82739 - Page 10 of 12

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

SARA SECTION This product does not contain "toxic" chemicals subject to the

313: requirements of section 313 of Title III of the Superfund Amendments

and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

CERCLA: Based on the ingredients listed in SECTION 2, this product does not

contain any "hazardous substances" listed pursuant to the

Comprehensive Environmental Response, Compensation and Liability

Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

TSCA: All the components of this product are listed on, or are automatically

included as "naturally occurring chemical substances" on, or are exempted from the requirement to be listed on, the TSCA Inventory.

CALIFORNIA: This product is not for sale or use in the State of California.

CANADIAN REGULATIONS

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

CANADIAN
ENVIRONMENTAL
PROTECTION
ACT (CEPA):

All the components of this product are listed on, or are automatically included as "substance occurring in nature" on, or are exempted from the requirements to be listed on, the Canadian Domestic Substances List (DSL).

MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

SECTION 16. OTHER INFORMATION

REVISION INFORMATION: Regulatory Update. Regulatory update, updated to ANSI

Z400.1-2004 format. This MSDS has been revised in the

following sections: Section 1 (Dates), Section 2

(Composition updated), Section 3 (switched to Emergency Overview), Section 4 (Phone Numbers), Section 5 (Fire Fields), Section 8 (Exposure Limits added), Section 11 (Toxicology fields updated), Section 12 (Ecotoxicity, fields

updated), Section 16 (Revision Information).

LABEL/OTHER INFORMATION: Not available.

User assumes all risks incident to the use of this (these) product(s). To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either express or implied, or merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers. The data contained on this sheet apply to the product(s) as supplied to the user.

©2007 Printed in the USA.